




Questions?

For customer service please call us at 1-310-787-1100
Office Hours: 8:00 a.m. – 5:00 p.m. PST Monday-Friday
E-mail: hello@euricompany.com



LED 6 CCT Half Cylinder Wall Sconce

PLEASE REVIEW THE INSTRUCTIONS AND WARNINGS LISTED BELOW PRIOR TO PROPER INSTALLATION

WARNINGS	CAUTIONS
<ul style="list-style-type: none"> • Risk of fire / electrical shock • LED Fixture installation requires knowledge of luminaire electrical systems. • Risk of electric shock – disconnect power at source before installation • Do not make or alter any open holes in an enclosure of wiring or electrical components during installation. • If lamp or luminaire exhibits abnormal operation (buzzing, flickering, minimal light, etc.), turn off power, remove lamp and contact us. For more information please visit www.euricompany.com or email hello@euricompany.com 	<ul style="list-style-type: none"> • Do not use with dimmers. • Do not look directly at the operating LED Tube. • Do not touch this product with wet hands. • Do not disassemble, repair or alter lamp. • Designed for indoor applications only. • Suitable for wet locations. • The luminaires shall be grounded. • Be careful not to touch the lamp pins to the metal housing when installing. • This Device is not intended for use with emergency exits or emergency lights.

INSTALLATION INSTRUCTIONS			
<p>1</p> <p>1. Remove the backplate.</p>	<p>2</p> <p>2. Install the mounting plate onto the junction box(not included).</p>	<p>3</p> <p>3. Connect the wires, attach the backplate, and tighten the nuts.</p>	<p>4</p> <p>4. Apply glue or waterproof silicone near the backplate. Done.</p>
USE THE SENSOR COVER		CCT SELECT SWITCH	
	<p>1. The light will turn on at dusk and remain on through the night until dawn. The light will remain off throughout the day, until dusk.</p> <p>2. At this time if the light is strong, please cover the sensor cover, after 15 seconds the light is on, then the installation is correct.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>NOTE: If you want to use the DUSK TO DAWN function, please remove the sensor cover. After commissioning the fixture is completed.</p> </div>		<p>Choose your preferred color temperature between 2700K, 3000K, 3500K, 4000K, 5000K, and 6500K with switch.</p>